

## Register Roam Miner on the Roam App

#### Step 1:

Download the Roam App and set up your account.

#### Step 2:

Allow connection to OpenRoaming WiFi.

#### Step 3:

Allow Roam to access your location.

Step 4:

On the Home page, tap "My Miner."

#### Step 5:

Tap "Register Miner" on the page.







La Li Que de la Carte de la Ca

Mitchell Bight Richmond Cichings Ciching Cichings Cichings Cichings Cichings Cichings Ciching

#### Step 6:

Connect to the same network with your Roam miner.





Tap 'Register' to proceed. (Your Roam miner will be automatically detected in the app.)

Registe

G Refresh

Step 8: Fill out required

tap 'Next'.

information and then

Step 9:

Tap 'Done' to complete the registration.







# Roam Rainier MAX60 Setup Instruction

### **Initial Setup**

Follow the below instructions to set up your miner:

#### Step 1:

Connect one end of the Ethernet cable provided in the box to the WAN port present at the back of the miner.

#### Step 2:

Power up your miner by plugging the power cord to the router and power supply.

#### Step 3:

Wait for the indicator light on the miner to change from red to white, indicating successful activation.

#### Step 4:

0

Connect your miner to your computer using the Ethernet cable provided. You can use any of the 4 Ethernet ports on the miner.







#### Step 5:

Open your web browser and enter **192.168.1.1** or **192.168.21.1** into the address bar.



#### Step 6:

Log into the miner configuration portal by using the username 'admin' and password located on the back of the miner.

٠	 a	A Not Second	382.388.3.106(apr)						(be . 🕸	ш	Ð	4	0	feinench te antiere 1
				7	$\sim$	-								
				6	2	20	am							
						lingh)								
						v MotaBia	or Salas							

#### Step 7:

Change your miner configuration portal password by clicking 'System' tab, then 'User' > 'Change' > 'Password'. The username 'admin' is not changeable.

← + Ø & Aint Servers 192.10	58.1.19(systemiliae		04 \$	 🗿 Aslanti to upiten 🌓
GB4-AA-A4-40-02-D0	Addition			•• •
O fintes -				
de sou		Corps (Salas		
(₹. WE)				
25 Front				
d) Server Servers				
C Selen -				
( Berlerit				
00000	Charge			
Gegenne	Usenave-			
function / Remaining				
	Patersta -			
	ACL group -			
		Garof (05)		

\* Changing your Admin Panel password is recommended for security purposes.

#### Step 8:

To change the hostname of your network, click 'System' > 'System'. Then press 'Save & Apply'. Changing your hostname is optional.

	GB.1.19yvystera	Withers			6.18	<b>n</b> 1		(Belauton ta spates 1)
084-44-40-02-00								90 × 0
-	Hostiane *							
O linna -	Timestre							
at LAN							Ser	& Aschy
¢ wii								
Sa frend								
🖶 Splast fanner								
Distant 7								
1.99993								
User								
Upgrade								
Backup / Hestore								



## Changing Your Miner's Network Names (SSIDs)

#### Your miner will provide three separate WiFi networks:

'Roam-Free', 'Roam-xxxxxx' and 'Roam-OpenRoaming'.'Roam-Free' is an open network that becomes available to other users only when you enable it through the miner configuration portal. 'Roam-xxxxxx' is a private WiFi network created for personal use, allowing you to set up a password for added security. 'Roam-OpenRoaming' is the OpenRoaming compatible network designed for mining.

### Follow the below instructions to change your miner's network SSIDs and WiFi password:

#### Step 1:

Complete the 'Initial Setup' using instructions provided in steps 1 to 6 to log into your miner's configuration portal.

#### Step 2:

Click the 'WiFi' tab. You'll see 3 setup menus for the different networks provided by your miner. Corresponding to the network types, their default SSIDs will be 'Roam-Free', 'Roam-xxxxxx', and 'Roam-OpenRoaming'.

#### Step 3:

You can change the network SSID and password here then click on the 'Save & Apply'.

+ → C (▲ Not Secure 192.168	1.5/#/will	🖘 🖈 🔯 🗂 🖙 🕕 Relaunch to update 🗄
84-AA-A4-40-02-D0	Free WiFi	<b>*●</b> <sup>7</sup> * ©
Status ¥	SSID * Roam-4002D0 -Free	
음 LAN	Password Leave blank to disable encryption	a
중 WiFi 🎆 Firewall	Enable 🔘	
😨 Splash Screen	Private WiFi	
	SSID * Roam-4002D0	
	Password	а.
	Enable	
	OpenRoaming WiFi	
	SSID * Roam-4002D0 -OpenRoaming	
		Save & Apoly

\* Changing your Admin Panel password is recommended for security purposes.



## Customizing Your WiFi Splash Screen

'Roam-Free' is an open network that can be accessed via a splash screen menu upon initial connection. This landing page can be customized with your preferred image. For users connecting to 'Roam-Free' provided by your miner, they will be presented with a splash screen upon initial connection.

### Follow the below instructions to customize the image and link presented to users on this page:

#### Step 1:

Follow the 'Initial Setup' instructions provided in steps 1 to 6 to log into your miner's configuration portal. Step 2:

Click Splash Screen'.

#### Step 3:

Upload the banner image and the link presented on your network's splash screen. Click 'Save & Apply'.

